



Advanced Elevator Systems

### Serenus LULA Commercial Hydraulic Elevator

#### Standard Features:

- 86" or 90" cab height
- 1400 lbs. (635 kg) rated load
- 30 fpm. (0.15 m/s) maximum speed
- 25 ft. (7.62 metre) maximum travel (This measurement can be exceeded dependent on local codes)
- Raised plastic laminate fire rated cab panels
- Plastic laminate ceiling with 4 potlights
- Automatic control UL/CSA listed
- 14" pit depth minimum
- 1:2 cable hydraulic drive
- Over speed valve
- Instantaneous safety device
- Emergency battery lowering
- Auto cab lights
- Solid Bumpers
- Car top inspection station
- Stainless steel control panel and trim
- Final limit switch
- Super-hush exclusive hydraulic pump unit of compact design & quiet operation.
- ADA phone
- Direction indicators in cab
- Automatic 2 speed doors (36" x 80" OR 36" x 84" Prime Coat)
- Arrival gongs in cab
- Stainless Steel Handrail

#### Optional Features:

The following additional features are available to help you customize your elevator:

- 96" cab height
- Custom cab sizes\* (\*Type A & B only – Up to 18 sq. ft.)
- Stainless Steel cab walls
- Stainless Steel frame with glass cab wall inserts
- Milled Plastic Laminate walls
- Hall station with Digital Position Indicator

- Overspeed governor
- Keyed hoistway access
- 5 HP motor
- LED underlit suspended ceiling
- Automatic home landing features
- Braille plates on cab operating panel and hall stations
- Automatic 3 speed doors
- Low overhead restrictor
- Low profile door operators
- Exit Hatch
- Additional Handrail
- In cab fan
- Independent Service
- Bronze package (Control panel, handrail, hall stations, potlights)
- Brass package (Control panel, handrail, hall stations, potlights)
- Stainless Steel cab and landing doors